



## PORTABLE TRANSFER KITS FOR GREASE



### PORTABLE PNEUMATIC 20KG DRUM KIT: FLX-4920CE

Mobile pneumatic grease supply kit with trolley.

- Pneumatic grease pump FLX-4020
  - Ratio 50:1
  - 400 bar max
  - 2400g/min
- Pressure regulator FLX-7200
- 3 m – high pressure hose 1/4" FLX-4503
- High pressure grease control gun, 300 mm – steel braid outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler FLX-4205
- High pressure Z – swivel FLX-4221
- Follower plate, ø 310 - 260 mm FLX-4314
- Metal drum cover, ø 330 – 290 mm FLX-4302
- Trolley with 2 wheels 4351

Weight 13kg

Dimensions 510Lx690Wx690H (mm)

---



### PORTABLE PNEUMATIC 50KG DRUM KIT: FLX-4960C

Mobile pneumatic grease supply kit with trolley.

- Pneumatic grease pump FLX-4060
  - Ratio 50:1
  - 400 bar max
  - 2900g/min
- Pressure regulator FLX-7200
- 3 m – high pressure hose 1/4" FLX-4503
- High pressure grease control gun, 300 mm – steel braid outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler FLX-4205
- High pressure Z – swivel FLX-4221
- Follower plate, ø 390 - 325 mm FLX-4317
- Metal drum cover, ø 400 – 360 mm FLX- 4305
- Trolley with 2 wheels FLX-4350

Weight 15kg

Dimensions 510Lx690Wx690H (mm)

---



### PORTABLE PNEUMATIC 180KG DRUM KIT: FLX-4911

Mobile pneumatic grease supply kit with trolley.

- Pneumatic grease pump FLX-4080
  - Ratio 50:1
  - 400 bar max
  - 2900g/min
- Pressure regulator and air filter with moisture separator FLX-7180
- Open hose reel FLX-9016
- 15 m – high pressure hose 1/4" FLX-4515
- 3 m – connection hose 1/4" FLX-4503
- High pressure grease control gun, 300 mm – steel braid outlet hose ø ext. 10 mm and 4 - jaws - hydraulic coupler FLX-4205
- High pressure Z – swivel FLX-4221
- Follower plate, ø 590 - 540 mm FLX-4319
- Metal drum cover, ø 600 – 560 mm FLX-4308\*
- Heavy duty trolley with 4 wheels and grate FLX-4389

Weight 49kg

Dimensions 900Lx1030Wx1400H (mm)

## STATIONARY TRANSFER KITS FOR GREASE



### PNEUMATIC GREASE SUPPLY KIT

Pneumatic grease transfer kit for the refilling of centralized lubrication systems. Consisting of:

- Pneumatic 25:1 - grease pump
- Metal drum cover
- Follower plate
- 2 m - rubber hose ø 1/2" and quick coupling.
- Suitable for grease up to a viscosity of NLGI 3.
- Output 7000g/stroke

**FLX-4923:** For 20kg drum

**FLX-4963:** For 50kg drum

**FLX-4983:** For 180kg drum



#### PNEUMATIC GREASE SUPPLY KIT FOR 180KG DRUM FLX-4995

Stationary pneumatic grease supply kit for 180 kg – drums with hose reel for wall or pillar installation Consisting of:

- Pneumatic grease pump FLX-4080
  - Ratio 50:1
  - 400 bar max
  - 2400g/min
- Pressure regulator and air filter with moisture separator FLX-7180
- Open hose reel FLX-9016
- 15 m – high pressure hose 1/4" FLX-4515
- 3 m – connection hose 1/4" FLX-4503
- High pressure grease control gun, 300 mm – steel braid outlet hose  $\varnothing$  ext. 10 mm and 4 - jaws
- hydraulic coupler FLX-4205
- High pressure Z – swivel FLX-4221
- Follower plate,  $\varnothing$  590 - 540 mm FLX-4319
- Metal drum cover,  $\varnothing$  600 – 560 mm FLX-4308

Weight 36kg



#### HEAVY INDUSTRIAL GREASE SUPPLY SYSTEM FOR 180KG DRUM FLX-4999/200INP

Bulk grease supply system consisting of a special pump lifting device suitable for heavy industrial **"PowerBull"** pneumatic grease pumps. Includes a grease compacting system that works based on a pneumatic circuit which is activated by a control valve.

For the use with grease pump models FLX-4046, FLX-4047, FLX-4048, FLX-4049, FLX-4050. The kit does **not** include the pneumatic grease pump.

- **Pressure pneumatic circuit:** 1 – 3 bar
- **Pressure compacting system:** 1 bar = 50 kg pressure
- **Suitable for drums:** 180 kg

Dimensions 1090Lx630Wx1900H (mm)

Weight 220 kg